



Belt Lengths:
 Speed 1 (1 to 2): 332mm
 Speed 2 (1 to 1): 330mm
 Speed 3 (2 to 1): 332mm
 [13 inches = 330mm]
 Part Number: PJ330/3

Position Number	Primary Pulley Diameter	Primary Pitch Diameter	Secondary Pitch Diameter	Drive Ratio	Calculated Spindle RPM				
					Note: Recommended 7,000 Max Spindle RPM Bearing Max: 10,000 RPM				
> Motor Shaft RPM >					200	1,400	2,600	3,800	5,000
XL Timing Pulley Set									
Primary Shaft RPM (see Jack-shaft)					200	1,400	2,600	3,800	5,000
1	TEETH	24.00	24.00	1.000	200	1,400	2,600	3,800	5,000
Jack-shaft reduction		1.00	1.00	1.000					
Custom three groove Pulley set for 3PJ Ribbed Belt									
Primary Shaft RPM (see reduction)					200	1,400	2,600	3,800	5,000
1		27.5	30.00	60.00	0.500	100	700	1,300	1,900
2		42.5	45.00	45.00	1.000	200	1,400	2,600	3,800
3		57.5	60.00	30.00	2.000	400	2,800	5,200	7,600
Jack-shaft reduction		1.00	1.00	1.000					

This document/file is placed in the **PUBLIC DOMAIN**. The author assumes no liability for the accuracy, fitness or application of the information or design herein.
 Lewis Balentine, Houston, Texas, 15 February 2020
 Unless otherwise noted all dimensions are in millimeters.